


Corona 2

powerlite®

28W, 38W & 55W TC-DD
Surface and Pendant Mounted Luminaire



Aluminium housing and trim with opal polycarbonate clip in cover for 28, 38 and 55W 2D lamps.

- High Frequency electronic control gear as standard
- Polycarbonate cover
- 3500K lamp included
- Attractive spill light feature



Lamp (Inc.)	White	Brass	Chrome	Steel
28W TC-DD	TLC28HF	TLC29HF	TLC30HF	TLC31HF
38W TC-DD	TLC38HF	TLC39HF	TLC40HF	TLC41HF
55W TC-DD	TLC55HF	TLC59HF	TLC60HF	TLC61HF


Options & Accessories **Code**

Emergency Lighting Version
3 hour maintained emergency version 28W & 38W only
The emergency module and batteries are fully integral. Suffix /SC3

28W versions suitable for high ambient temperatures Ta 35 max.
38W versions Ta 30 max.

Pendant Unit
Corona 2 with pendant mounting kit
Adjustable length (1.5m max) with 3 core cable. Suffix /PK

Semi-recessing Kit Suffix /RK



**55W, 38W & 28W
Opal Cover**

H m	55W	E Lux 38W	28W	Dia m
1.0	548	401	315	2.9
2.0	137	100	79	5.7
3.0	60	45	35	8.5
4.0	34	25	20	11.4
5.0	22	16	13	14.3

I_{max} 145 cd/klm cone 110°