


# Corona 6

powerlite®

## 16W TC-DD Surface Mounted Luminaire



Neat stylish and compact range of luminaires for general use in more discerning installations. Localised wall or ceiling lighting in banks, building societies, hotels, bars, porches etc.

- IP44 protection for use in bathrooms Zone 2
- Injection moulded polycarbonate with choice of snap on opal or prismatic cover
- Available in 3 trim finishes
- Corona 5 available with integral maintained emergency
- Supplied complete with 3500K lamp


Trim	High Frequency		Switchstart	
	Opal	Prismatic	Opal	Prismatic
Chrome	PDR718HF	PDX718HF	PDR718	PDX718
White	PDR717HF	PDX717HF	PDR717	PDX717
Brass	PDR716HF	PDX716HF	PDR716	PDX716

### Options & Accessories

**Emergency Lighting Version EM3**  
 Maintained 3-hour emergency versions are supplied with the emergency module and batteries in a **separate steel enclosure** connected to the luminaire via 0.5m flexible conduit wiring harness. Suffix /EM3

**Power Factor Correction**  
 Available as an optional extra for all fluorescent versions Suffix /PF

**Brass Finial Kit**  
 Natural brass colour BFK1  
 Requires a 10mm diameter hole to be drilled in the centre of the diffuser



### Corona 6 38W, 28W & 16W Prismatic Cover

H m	E Lux			Dia m
	38W	28W	16W	
1.0	487	352	190	3.4
2.0	122	88	48	6.9
3.0	54	39	21	10.4
4.0	30	22	12	14
5.0	19	14	8	17.3

I<sub>max</sub> 171 cd/klm cone 120°