

Microna 4

powerlite®

12V 50W MR16 Track and Surface Mounted Spotlights



Retro styled die-cast aluminium head. Fully encloses lamp for where extraneous light is undesirable. Ideal for general display lighting in shops, exhibitions and galleries etc.

- 12V, 50W (max) GU 5.3 (MR16) reflector lamps (not included)



Surface Mounted

- Steel fixing plate with terminal block
- Remote 12V transformer required
- Electrical protection Class III

White	Black	Aluminium	Fig.
ULS50	ULS51	ULS54	1




Sirius 1 Low Voltage Track Mounted (i)

White	Black	Aluminium	Fig.
ULT50	ULT51	ULT54	2

Mains Voltage, Surface Mounted with Integral Electronic Transformer

- Polycarbonate transformer housing
- Electrical protection Class II
- Dimmable using a **'trailing edge' type dimmer only**
- Thermal, overload and short circuit protected


White	Black	Aluminium	Fig.
UTS50	UTS51	UTS54	3




Microna 4 Pendant Drops (for Microna 4 versions)

- Available with a range of drop rods in various lengths
- To specify, add the appropriate suffix for the required length eg. ULS50/300

Length	200mm	300mm	400mm	500mm	1000mm
Suffix	/200	/300	/400	/500	/1000



Microna 4 Pendant Reversed Head Configuration
Suffix R (eg. ULS50/300R)



3 x 12V 50W MR16 Microna 4 Triple

- Remote 12V transformer required
- Electrical protection Class III

White	Black	Aluminium
ULS300	ULS301	ULS304

Microna 4

12V 50W MR16 Track and Surface Mounted Spotlights

powerlite®



Microna 4 Picturelite

- Ideal for lighting indoor signs, pictures, wall displays, exhibition areas, showrooms, reception areas, galleries etc
- ø85mm Steel fixing plate with terminal block
- Electrical protection Class III
- Remote 12V transformer required (pg 37)
- Length 400mm

White	Black	Aluminium
USP500	USP501	USP504



Microna 4 Exhibition

- Clips to panels up to 40mm thick to provide quick change of lighting position for exhibition stand and show areas
- Remote 12V transformer required
- Length 500mm
- Electrical protection Class III

White	Black	Aluminium
UBD500	UBD501	UBD504



Microna 4 Picturelite with Integral Electronic Transformer

- Electrical protection Class II
- Dimmable using a **'trailing edge' type dimmer only**
- Thermal, overload and short circuit protected
- Length 430mm

White	Black	Aluminium
USL500	USL501	USL504