

# REGOR LED 9

High quality LED floodlight. IP65 industrial body with a range of light outputs.

## FEATURES

- Tridonic constant current control gear
- Photocell available
- Up to 27,4082 luminaire lumens
- 3K, 4K & 5K colour temperature options



## TECHNICAL DETAILS

| Part Number | Description         | Replaces | Weight (kg) | No. Per 10A Breaker | Inrush Current (A) | Circuit Watts (W) | Board Lumens | Luminaire Lumens | LI/cw |
|-------------|---------------------|----------|-------------|---------------------|--------------------|-------------------|--------------|------------------|-------|
| R9L1004K    | 100W LED Floodlight | 250W HQI | 9           | 6                   | 103A 167µs         | 100               | 14166        | 12041            | 120.4 |
| R9L1504K    | 150W LED Floodlight | 400W HQI | 9           | 6                   | 124A 208µs         | 150               | 21249        | 18062            | 120.4 |
| R9L2004K    | 200W LED Floodlight | 400W SON | 9           | 6                   | 172A 228µs         | 200               | 28332        | 24082            | 120.4 |

## OPTIONS AND ACCESSORIES

- PC** Integral Photocell  
**3K** 3000K Colour Temperature  
**5K** 5000K Colour Temperature

## PHOTOMETRIC AND DIMENSION

