

# CORONA LED 1

Slimline, flat circular surface mounted luminaire for use in corridor or communal areas. The LED diffuser provides even distribution with minimal glare.

## FEATURES

- Up to 2732 luminaire lumens
- Various trim colours available
- Integral controls and dimming
- Integral emergency options



## TECHNICAL DETAILS

Part Number	Description	Replaces	Weight (kg)	No. Per 10A Breaker	Inrush Current (A)	Circuit Watts (W)	Board Lumens	Luminaire Lumens	LI/cW
C1LW48504K-HE	White Body	28W 2D	2.9	65	8A 80µs	10	1734	1301	130.1
C1LW48704K-HE	White Body	38W 2D	2.9	40	10A 100µs	14	2428	1821	130.1
C1LW48104K-HE	White Body	38W 2D	2.9	40	10A 100µs	21	3642	2732	130.1

## OPTIONS AND ACCESSORIES

- EM** Integral Emergency (1W)
- EMST** Integral Emergency Self Test (1W)
- CF** Corridor Function
- MWP** Remotely Programmable Microwave
- DD** SwitchDIM/DALI
- WL** Wireless Control System
- WLEM** Wireless Monitored Emergency
- 3K** 3000K Colour Temperature
- 5K** 5000K Colour Temperature

## PHOTOMETRIC AND DIMENSION

