

CORONA LED 2

Fitzgerald Equivalent: Silvarus

Surface LED luminaire with extended trim, backlight and LED diffuser.

FEATURES

- Halo effect backlight
- Up to 2732 luminaire lumens
- Integral controls and dimming
- Integral emergency options
- Various trim colours available



LED

IP20

2D
EQUIVALENT

5 YEAR
WARRANTY

TECHNICAL DETAILS

Part Number	Description	Replaces	Weight (kg)	No. Per 10A Breaker	Inrush Current (A)	Circuit Watts (W)	Board Lumens	Luminaire Lumens	Ll/cw
C2LW48504K-HE	White Trim	28W 2D	2.8	65	8A 80µs	10	1734	1301	130.1
C2LC48504K-HE	Chrome Trim	28W 2D	2.8	65	8A 80µs	10	1734	1301	130.1
C2LS48504K-HE	Brushed Steel Trim	28W 2D	2.8	65	8A 80µs	10	1734	1301	130.1
C2LW48704K-HE	White Trim	38W 2D	2.8	40	10A 100µs	14	2428	1821	130.1
C2LC48704K-HE	Chrome Trim	38W 2D	2.8	40	10A 100µs	14	2428	1821	130.1
C2LS48704K-HE	Brushed Steel Trim	38W 2D	2.8	40	10A 100µs	14	2428	1821	130.1
C2LW48104K-HE	White Trim	38W 2D	2.8	40	10A 100µs	21	3642	2732	130.1
C2LC48104K-HE	Chrome Trim	38W 2D	2.8	40	10A 100µs	21	3642	2732	130.1
C2LS48104K-HE	Brushed Steel Trim	38W 2D	2.8	40	10A 100µs	21	3642	2732	130.1

Colour Filter

B Blue Filter **G** Green Filter **R** Red Filter **C** Clear Filter

OPTIONS AND ACCESSORIES

- EM** Integral Emergency (1W)
- EMST** Integral Emergency Self Test (1W)
- CF** Corridor Function
- MWP** Remotely Programmable Microwave
- DD** SwitchDIM/DALI
- WL** Wireless Control System
- WLEM** Wireless Monitored Emergency
- 3K** 3000K Colour Temperature
- 5K** 5000K Colour Temperature

PHOTOMETRIC AND DIMENSION

