

# CORONA LED 3

Surface halo effect LED bulkhead fitting.  
 Steel base with LED opal polycarbonate diffuser.

## FEATURES

- Halo effect backlight
- LED opal diffuser with 75% LOR
- 3K, 4K & 5K LEDs available
- Integral control options



## TECHNICAL DETAILS

Part Number	Description	Replaces	Weight (kg)	No. Per 10A Breaker	Inrush Current (A)	Circuit Watts (W)	Board Lumens	Luminaire Lumens	LI/cw
C3LW48504K-HE	White Body	28W 2D	2.5	65	8A 80µs	10	1734	1301	130.1
C3LC48504K-HE	Chrome body	28W 2D	2.5	65	8A 80µs	10	1734	1301	130.1
C3LS48504K-HE	Brushed Steel body	28W 2D	2.5	65	8A 80µs	10	1734	1301	130.1
C3LW48704K-HE	White Body	38W 2D	2.5	65	10A 100µs	14	2428	1821	130.1
C3LC48704K-HE	Chrome body	38W 2D	2.5	65	10A 100µs	14	2428	1821	130.1
C3LS48704K-HE	Brushed Steel body	38W 2D	2.5	65	10A 100µs	14	2428	1821	130.1
C3LW48104K-HE	White Body	38W 2D	2.5	65	10A 100µs	21	3642	2732	130.1
C3LC48104K-HE	Chrome body	38W 2D	2.5	65	10A 100µs	21	3642	2732	130.1
C3LS48104K-HE	Brushed Steel body	38W 2D	2.5	65	10A 100µs	21	3642	2732	130.1

Colour Filter

**B** Blue Filter      **G** Green Filter      **R** Red Filter      **C** Clear Filter

## OPTIONS AND ACCESSORIES

- EM** Integral Emergency (1W)
- EMST** Integral Emergency Self Test (1W)
- CF** Corridor Function
- MWP** Remotely Programmable Microwave
- DD** SwitchDIM/DALI
- WL** Wireless Control System
- WLEM** Wireless Monitored Emergency
- 3K** 3000K Colour Temperature
- 5K** 5000K Colour Temperature

## PHOTOMETRIC AND DIMENSION

