

CORONA LED 4

Fitzgerald Equivalent: Nemesis

Surface and semi-recessed LED decorative bulkhead fitting with a spun body and LED polycarbonate opal diffuser.

FEATURES

- Surface or semi-recessed options
- LED opal diffuser with 75% LOR
- Integral control options
- Semi-recessing option
- 3K, 4K & 5K LEDs



LED

IP20

2D
EQUIVALENT

5 YEAR
WARRANTY

TECHNICAL DETAILS

Part Number	Description	Replaces	Weight (kg)	No. Per 10A Breaker	Inrush Current (A)	Circuit Watts (W)	Board Lumens	Luminaire Lumens	LI/cW
C4LW48504K-HE	White Trim	28W 2D	2.5	65	8A 80µs	10	1734	1301	130.1
C4LC48504K-HE	Chrome Trim	28W 2D	2.5	65	8A 80µs	10	1734	1301	130.1
C4LS48504K-HE	Brushed Steel Body	28W 2D	2.5	65	8A 80µs	10	1734	1301	130.1
C4LW48704K-HE	White Trim	38W 2D	2.5	65	10A 100µs	14	2428	1821	130.1
C4LC48704K-HE	Chrome Trim	38W 2D	2.5	65	10A 100µs	14	2428	1821	130.1
C4LS48704K-HE	Brushed Steel Body	38W 2D	2.5	65	10A 100µs	14	2428	1821	130.1
C4LW48104K-HE	White Trim	38W 2D	2.5	65	10A 100µs	21	3642	2732	130.1
C4LC48104K-HE	Chrome Trim	38W 2D	2.5	65	10A 100µs	21	3642	2732	130.1
C4LS48104K-HE	Brushed Steel Body	38W 2D	2.5	65	10A 100µs	21	3642	2732	130.1

OPTIONS AND ACCESSORIES

EM	Integral Emergency (1W)
EMST	Integral Emergency Self Test (1W)
CF	Corridor Function
MWP	Remotely Programmable Microwave
DD	SwitchDIM/DALI
WL	Wireless Control System
WLEM	Wireless Monitored Emergency
SR	Semi-recessed option
3K	3000K Colour Temperature
5K	5000K Colour Temperature

PHOTOMETRIC AND DIMENSION

