

REGOR LED 15

The Regor LED 15 is a robust IP65 surface mounted luminaire designed for external applications.

FEATURES

- Die-cast aluminium base
- Integral sensor option
- Conduit side entry points
- Integral emergency option



LED

IP65

2D
EQUIVALENT

5 YEAR
WARRANTY

TECHNICAL DETAILS

Part Number	Description	Replaces	Weight (kg)	No. Per 10A Breaker	Inrush Current (A)	Circuit Watts (W)	Board Lumens	Luminaire Lumens	LI/cW
R15W48504K-HE	10W White Square Body	28W 2D	3.18	65	8A 80µs	10	1734	1335	133.5
R15W48704K-HE	14W White Square Body	38W 2D	3.18	40	10A 100µs	14	2428	1870	133.5
R15B48504K-HE	10W Black Square Body	28W 2D	3.18	65	8A 80µs	10	1927	1484	133.5
R15B48704K-HE	14W Black Square Body	38W 2D	3.18	45	10A 100µs	14	2428	1870	133.5

OPTIONS AND ACCESSORIES

EM	Integral Emergency (1W)
EMST	Integral Emergency Self Test (1W)
PC	Integral Photocell
CF	Corridor Function
MWP	Remotely Programmable Microwave
WL	Wireless Control System
WLEM	Wireless Emergency Monitoring
DD	SwitchDIM/DALI
3K	3000K Colour Temperature
5K	5000K Colour Temperature

PHOTOMETRIC AND DIMENSION

